



Simple and easy appearance, in line with contemporary aesthetic concept. Ideal choices of size and design, this range is suitable for every wall. The product has the structure and appearance design patent. can be easily installed in any type of space, to create amazing light effects.

FIELDS OF APPLICATION:


Living spaces, villas, residential, offices, showrooms, hotels, restaurants, buildings, hospitals, shopping malls, supermarket, convention centers, galleries, etc.

The RIA Recessed Frame adaptable for indoor applications.

High Lumen Efficacy 115 lm/W - UGR<19
 Body - Die cast aluminum housing with solvent free powder coating
 Reflector - Anodized aluminum
 Diffuser - polycarbonate pattern lens
 Glowing Wire Test - 850°
 Temperature - of=20 °C ~ of max=50 °C

Model --- **RIA**

RIA-A-1-15-27-W-3W



RIA	X	X	X	X	X	Size	A							
						Driver	1	2	3	4	5	6	7	
							On/Off	Dali	1-10	Phase Dimming	RGBW	Casambi	Tuya	
						Beam Angle	15° 24° 36° 60°							
						Kelvin	27	30	40	50	60	TUN	1	2
							2700k	3000k	4000k	5000k	6000k	Tunable	RGB	RGBW
						Finishing	W B S X							
							white black silver as per requested							
						Wattage	3	5	8	10	12	18	20	

Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.


A - Ø 65-50mm 55mm

IP20 COB McA Step 3 220-240V







Relative spectral perception of brightness and melanopic effect


Effect as a percentage



Explanation of the three curves:
 V(A) = Perception of brightness, daytime seeing with the cones
 V'(λ) = Nighttime seeing with the rods
 S_M(λ) = Melanotin suppression with the photosensitive ganglion cells



Available Accessories



LED life time		Operating time 1.000 h											
Lamp Lumen Maintenance Factor	Lamp Survival Factor	1	10	20	30	40	50	60	70	80	90	100	
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64	0.60
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.98	0.98
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.99	0.99

