

LFIN-LD-ARMADA-D-3K



Description:

ARMADA is a out side beam direction adjustable Inground light typically feature durable, weather-resistant housings suitable for outdoor use. Excellent heat dissipation. It include features such as corrosion resistance , dustproof, anodized and polished, sand blasted, not easy to rust and fade. Toughened glass surface, with high hardness, not easy to break. It comes with different CCT and R/G/B LED sources and various beam angles this family is a perfect solution to the requirement. It has very wide application like For landscape lighting, garden lighting, horticultural engineering design, public fountain square Lighting.



Product Specifications:

Front cover : Stainless Steel SUS 316
 Housing : Die cast aluminum grey
 Coating: Powder Coating
 Glass : Tempered glass
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Inground
 Adjustable: Yes

Technical Specifications:

Wattage: 18- 24W
 Voltage: DC24V / 220-240V AC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 100lm/W
 Mac Adam: 3 Step
 Safety Class: III / II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years


Parameter:

Wattage(W)	:	18W / 24W
Finish	:	Stainless Steel SUS 316 (SS)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K / RGB / RGBW
Beam Angle	:	10° / 18° / 24° / 38° / 45° / 60°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX

Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
LFIN-LD-ARMADA-D-3K	18-18W(12X1.5W)	27-2700K	D-24VDC	10 - 10°	SS-Stainless Steel 316	1-ON/OFF
	24-24W(12X2W)	30-3000K		18 - 18°		2-DALI
		40-4000K		24 - 24°		3-0/1-10V
		60-6000K		38 - 38°		4-Phase cut
		92-RGB		45 - 45°		5-DMX
		93-RGB DMX		60 - 60°		
	82-RGBW					
	83-RGBW					

Photometric :



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

DMX

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
LFIN-LD-ARMADA-D-3K	18-18W(12X1.5W)	27-2700K	A-220-240VAC	10 - 10°	SS-Stainless Steel 316	1-ON/OFF
		30-3000K		25- 25°		2-DALI
		40-4000K		45 - 45°		3-0/1-10V
		60-6000K		60 - 60°		4-Phase cut 5-DMX