



CRI: 90
Led Qty: 320LEDS/M
Length/Reel: 5M - 10M
Width: 8MM
Working Temperature:- 20~50°C
Storage Temperature: -30~80°C
Voltage Range: 23 ~25V dc
Reverse Voltage: : 25V dc



IP20 COB 24V 320LED 8W/M

Technical drawing of the 5004mm Max Run cable assembly. The drawing shows a side view of the cable with a black outer jacket, a red inner jacket, and a yellow braided shield. The dimensions are as follows:

- Overall length: 5004mm (197.01") Max Run
- Inner jacket length: 360mm (14.17")
- Inner jacket thickness: 10mm (0.39")
- Inner jacket width: 100mm (3.93") Cutting Length
- Inner jacket width: 100mm (3.93")
- Inner jacket width: 100mm (3.93")
- Inner jacket width: 100mm (3.93")
- Inner jacket width: 100mm (3.93")



LED life time			Operating time 1.000 h										
Lamp Lumen Maintenance Factor			1	10	20	30	40	50	60	70	80	90	100
Lamp Survival Factor			1	1	1	1	1	1	1	1	0.99	0.99	0.99
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64	0.60
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.99	0.98
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80
		LSF	1	1	1	1	1	1	1	0.99	0.99	0.99	0.99

AC220
-240V

LM-80

